

Page 1/9

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Revision: 16.11.2023 Version number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: LuminaCast 5 Radiant Flow

Article number: LUC5RAFL

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Epoxy resin hardener

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

DIPON.DE Removable Automotive Coatings GmbH & Co. KG

Ringofenstr. 39

**D - 44287 DORTMUND** 

**DEUTSCHLAND** 

Further information obtainable from: Abteilung Produktsicherheit

1.4 Emergency telephone number: Während der normalen Öffnungszeiten: +49 231 187 30 332

#### **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1 H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

#### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

#### Hazard pictograms







GHS05

GHS07

GHS09

#### Signal word Danger

#### Hazard-determining components of labelling:

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Ethoxylatedamine

3-(aminomethyl)-3,5,5-trimethylcyclohexan-1-amine

(Contd. on page 2)



Page 2/9

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Version number 1 Revision: 16.11.2023

Trade name: LuminaCast 5 Radiant Flow

(Contd. of page 1)

#### **Hazard statements**

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or

shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

| Dangerous components:  | Dangerous components:  |          |
|--|--|----------|
| CAS: 2855-13-2<br>EINECS: 220-666-8<br>Index number: 612-067-00-9<br>Reg.nr.: 01-2119514687-32-xxx | 3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318; ♠ Acute Tox. 4, H302; Skin Sens. 1A, H317 ATE: LD50 oral: 1,030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 % | >10–≤40% |
| CAS: 39423-51-3<br>NLP: 500-105-6<br>Reg.nr.: 01-2119556886-20-xxx                                 | Ethoxylatedamine  Eye Dam. 1, H318;  Aquatic Chronic 2, H411;  Acute Tox. 4, H302; Acute Tox. 4, H312  | ≥25–≤40% |
| CAS: 68609-08-5<br>EC number: 614-657-1<br>Reg.nr.: REACH Annex V No. 4                            | 3-(aminomethyl)-3,5,5-trimethylcyclohexan-1-amine Skin Corr. 1, H314; Eye Dam. 1, H318   | ≥5–≤15%  |

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

#### After swallowing:

Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Page 3/9

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Version number 1 Revision: 16.11.2023

Trade name: LuminaCast 5 Radiant Flow

(Contd. of page 2)

#### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

#### 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

#### 5.3 Advice for firefighters

Protective equipment: Mouth respiratory protective device.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

#### 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

#### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

#### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection: Keep respiratory protective device available.

#### 7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information: The lists valid during the making were used as basis.

#### 8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

#### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 4)



Page 4/9

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Version number 1 Revision: 16.11.2023

Trade name: LuminaCast 5 Radiant Flow

(Contd. of page 3)

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use selfcontained respiratory protective device.

#### Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### Eye/face protection



Tightly sealed goggles

## **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

**General Information** 

Physical state Fluid
Colour: Clear
Odour: Amine-like
Odour threshold: Not determined.
Melting point/freezing point: Undetermined.
Boiling point or initial boiling point and boiling range >200 °C

Flammability Not applicable.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.Flash point:>100 °C

**Decomposition temperature:** Not determined.

pH at 20 °C 12.6

Viscosity:

Kinematic viscosity at 20 °C 1,330 s (DIN 53211/4)

Dynamic: Not determined.

Solubility

water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure at 20 °C: <1 hPa

Density and/or relative density

Density at 20 °C: 1.16 g/cm³
Relative density Not determined.

(Contd. on page 5)



Page 5/9

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Version number 1 Revision: 16.11.2023

Trade name: LuminaCast 5 Radiant Flow

(Contd. of page 4)

| Vapour density                                     | Not determined.                               |  |
|--|---|--|
| 9.2 Other information                              |   |  |
| Appearance:  |   |  |
| Form:  | Fluid   |  |
| Important information on protection of health      | h and   |  |
| environment, and on safety.                        |   |  |
| Ignition temperature:                              | Product is not selfigniting.                  |  |
| Explosive properties:                              | Product does not present an explosion hazard. |  |
| Solvent content:                                   |   |  |
| VOC (EC)   | 0.00 %  |  |
| Change in condition                                |   |  |
| Evaporation rate                                   | Not determined.                               |  |
| Information with regard to physical hazard classes |   |  |
| Explosives   | Void  |  |
| Flammable gases                                    | Void  |  |
| Aerosols   | Void  |  |
| Oxidising gases                                    | Void  |  |
| Gases under pressure                               | Void  |  |
| Flammable liquids                                  | Void  |  |
| Flammable solids                                   | Void  |  |
| Self-reactive substances and mixtures              | Void  |  |
| Pyrophoric liquids                                 | Void  |  |
| Pyrophoric solids                                  | Void  |  |
| Self-heating substances and mixtures               | Void  |  |
| Substances and mixtures, which emit flammable      | е   |  |
| gases in contact with water                        | Void  |  |
| Oxidising liquids                                  | Void  |  |
| Oxidising solids                                   | Void  |  |
| Organic peroxides                                  | Void  |  |
| Corrosive to metals                                | Void  |  |
| Desensitised explosives                            | Void  |  |

#### **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Harmful if swallowed.

| LD/LC50 values relevant for classification: |  |  |  |
|---|--|--|--|
| ATE (A                                      | cute Toxicity Estimates)                               |  |  |
| Oral  | LD50   1,219 mg/kg                                     |  |  |
| Dermal                                      | LD50 4,400 mg/kg                                       |  |  |
| 2055 42                                     | 2055 42-2-2 aminomethyd 2-5-5 trimethydoxolohoyydamina |  |  |

| 2855-13 | 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine |                   |
|---------|--|-------------------|
| Oral    | LD50   | 1,030 mg/kg (ATE) |

(Contd. on page 6)



Page 6/9

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Version number 1 Revision: 16.11.2023

Trade name: LuminaCast 5 Radiant Flow

(Contd. of page 5)

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/irritation Causes serious eye damage.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

#### **Endocrine disrupting properties**

None of the ingredients is listed.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

#### 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

#### 12.7 Other adverse effects

Remark: Toxic for fish

#### Additional ecological information:

#### **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

### \* SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| Europ | European waste catalogue |  |
|-------|--------------------------|--|
| HP6   | Acute Toxicity           |  |
| HP8   | Corrosive                |  |
| HP13  | Sensitising              |  |
| HP14  | Ecotoxic                 |  |

#### Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

(Contd. on page 7)



Page 7/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Revision: 16.11.2023 Version number 1

Trade name: LuminaCast 5 Radiant Flow

(Contd. of page 6)

#### **SECTION 14: Transport information**

| 14.1 UN number or ID number   |  |
|---|--|
| ADR, IMDG, IATA   | UN2289   |
| 14.2 UN proper shipping name<br>ADR<br>IMDG<br>IATA   | 2289 ISOPHORONEDIAMINE, ENVIRONMENTALLY HAZARDOUS ISOPHORONEDIAMINE Isophoronediamine                                  |
| 14.3 Transport hazard class(es)   |  |
| ADR   |  |
| Class<br>Label  | 8 Corrosive substances.  |
| IMDG, IATA  | ·  |
| Class<br>Label  | 8 Corrosive substances.  |
| 14.4 Packing group<br>ADR, IMDG, IATA   | III  |
| 14.5 Environmental hazards: Special marking (ADR):  | Product contains environmentally hazardous substances:<br>Ethoxylatedamine<br>Symbol (fish and tree)                   |
| 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category Segregation Code | Warning: Corrosive substances. 80 F-A,S-B A SG35 Stow "separated from" SGG1-acids                                      |
| 14.7 Maritime transport in bulk according to IMC instruments  | O<br>Not applicable.   |
| Transport/Additional information:   |  |
| ADR Limited quantities (LQ) Excepted quantities (EQ)  | 5L<br>Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| Transport category Tunnel restriction code  | 3<br>E   |
| IMDG<br>Limited quantities (LQ)   | 5L   |



Page 8/9

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Version number 1 Revision: 16.11.2023

Trade name: LuminaCast 5 Radiant Flow

(Contd. of page 7)

| Excepted quantities (EQ) | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
|--------------------------|--|
| UN "Model Regulation":   | UN 2289 ISOPHORONEDIAMINE, 8, III, ENVIRONMENTALLY HAZARDOUS   |

#### \* SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

| DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and |
|--|
| electronic equipment – Annex II  |
| None of the ingredients is listed.   |

#### **REGULATION (EU) 2019/1148**

## Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

#### Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

#### Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

| Classification according to Regulation (EC) No 1272/2008   |  |
|--|--|
| Acute toxicity - oral Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation Hazardous to the aquatic environment - long-term (chronic) aquatic hazard | The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. |

(Contd. on page 9)



Page 9/9

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Version number 1 Revision: 16.11.2023

Trade name: LuminaCast 5 Radiant Flow

(Contd. of page 8)

**Department issuing SDS:** 

Abteilung Produktischerheit

info@dipon.de

Contact:

DIPON.DE Removable Automotive Coatings GmbH & Co. KG

Ringofenstr. 39 D-44287 Dortmund www.dipon.de

Date of previous version: 13.11.2023

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of

Dangerous Goods by Road)

IMDĞ: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1: Skin corrosion/irritation – Category 1
Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
\* Data compared to the previous version altered.